



Brüel & Kjær Vibro



VIBROCONTROL 1000

On-site Machine Protection

VIBROCONTROL 1000



Permanent machine monitoring is in particular necessary for machines which are exposed to strong damaging influences and whose failure may result in high repair costs or substantial losses of production.

Typical applications in these cases are ventilators, fans, compressors, centrifuges, turbines, generators, mills and pumps.

VIBROCONTROL 1000

Depending upon the construction type, size and application conditions, one or more measurements types must be monitored. B&K Vibro offers a comprehensive palette of machine monitoring systems and thereby a tailor-made solution for every task.

The monitoring instruments of the VIBROCONTROL 1000 family are selected when a single measurement type is sufficient to guarantee reliable machine protection.


The measurement types

Absolute bearing vibrations



These are understood to be the measurable vibrations at the surface of the machine. They are a reliable criterion for assessment of the vibration behaviour of machines equipped with rolling-element bearings. The absolute bearing vibrations are acquired by utilization of VIBROCONTROL 1000 with vibration velocity sensors. The following measurements can be selectively monitored:

- RMS value of vibration velocity V_{RMS}
- Peak value of vibration displacement S_p

For assessment of bearing vibrations extensive experience is available, e.g. as published in DIN ISO 10816. This guideline recommends the "RMS value of vibration velocity" in the frequency range 10 to 1000 Hz as the measurement type.



VIBROCONTROL 1000 Technical Data

		1-channel absolute bearing vibrations
Order code	Typ	
VC-1000	CV-110 CV-116	
Inputs		
No. of vibration channels Sensor connections Sensor power Sensor OK monitoring	1 Vibration velocity sensors, e.g. VS-068, VS-069, VS-077, VS-079, VS-0168, VS-0169 None required Yes, cable damage	
Measurement types		
Measurement channels Measuring ranges	1-channel operation with continuous monitoring Vibration velocity: 0...2/5/10/20/50/100 mm/s Vibration displacement: 0...20/50/100/200/500/1000 μm Sensor with natural frequency $f_0 = 8 \text{ Hz}$: 10 ... 1000 Hz 1 ... 1000 Hz	
Frequency range ¹⁾	Sensor with natural frequency $f_0 = 15 \text{ Hz}$: 15 ... 1000 Hz 2 ... 1000 Hz	
Displacement measurement Bearing vibration measurement Measurement accuracy	Peak value of vibration displacement in μm RMS value of vibration velocity in mm/s 5% of measured value, additionally 3% of measuring range full scale	
Monitoring		
Alarm signalling Relay time delay Limit value relay	Alert and Danger alarm: Setting range between 10% ... 100% of measuring range full scale 1, 3, 10 s, 30 ms 2 relays, in normally energized or normally de-energized operation, latching or non-latching	
Outputs		
Analogue signal outputs	0/4...20 mA, Load $\leq 500 \Omega$ or 0...10 V (Load resistance $\geq 100 \text{ k}\Omega$)	
Power supply		
Mains power	CV-110 230/115 V AC, +10% / -15%, 50...60 Hz, appr. 10 VA CV-116 24 V DC (18...32 V), appr. 10 W	
Environmental conditions		
Operating temperature range Storage temperature range Humidity	0°C ... + 65°C - 40°C ... + 100°C Max. 95% non-condensing	
Mechanical data		
Housing Dimensions Cable feed	Rugged aluminium housing in protection class IP-65, total weight approx. 2.1 kg 220 x 120 x 90 (L x B x H) 8 x M 16 x 1.5 feed-through fittings	

¹⁾ selectively with or without frequency response linearization

Extent of delivery and order data

1. Monitoring electronics

consisting of:

A vibration monitoring instrument VIBROCONTROL 1000 with 2 user's instructions in German, English or French language (please specify language when ordering).

2. Vibration sensor

Vibration velocity sensor in standard form	VS-068	Horizontal measurement, 2-core, PTFE, 5 m cable with steel protective conduit, T _A - 40°C ... + 80°C, ²⁾
	VS-069	Vertical measurement, 2-core, PTFE, 5 m cable with steel protective conduit, T _A - 40°C ... + 80°C, ²⁾
Vibration velocity sensor in Ex form	VS-0168	Horizontal measurement, 3-core, PVC, 10 m cable T _A - 10°C ... + 70°C, ²⁾
	VS-0169	Vertical measurement, 3-core, PVC, 10 m cable T _A - 10°C ... + 70°C, ²⁾

¹⁾ Design inspection certificates, ATEX certification and data sheet available on our homepage for download.

²⁾ T_A operating temperature range.

3. Terminal protective housing

Rugged aluminium housing in IP-65 protection class, painted RAL 7001, with cable feed-throughs

Standard form	AC-2104	for max. 2 vibration sensors VS-068/069 or AS-022/030 weight appr. 1.2 kg
Ex form	AC-2103	for max. 2 vibration sensors VS-0168, VS-0169, weight appr. 420 g
4. Signal cable		
Standard form	AC-112	for vibration sensors AS-022/030 and VS-068/069, 4 x 0,5 mm ² , shielded, PVC black LIY (ST) Y, 7 mm Ø, T _A - 20°C ... + 70°C, ²⁾
Ex form	AC-180	for vibration velocity sensors, e.g. VS-0168/VS-0169 ¹⁾ , 3 x 0,75 mm ² shielded, PVC grey (N) YLHCY-J, 7 mm Ø, T _A - 10°C ... + 80°C, ²⁾

Brüel & Kjær Vibro A/S
 Skodsborgvej 307B
 2850 Nærum
 Denmark
 Tel.: +45 77 41 25 00
 Fax: +45 45 80 29 37
 info@bkvibro.com

Brüel & Kjær Vibro GmbH
 Leydheckerstraße 10
 64293 Darmstadt
 Germany
 Tel.: +49 (0) 6151 428 11 00
 Fax: +49 (0) 6151 428 12 00
 info@bkvibro.de

www.bkvibro.com

Order Data for VIBROCONTROL 1000

Series CV

<input type="checkbox"/>	A	Monitoring electronics	<input type="checkbox"/>	G	Limit relay 2
		110 with relays, power supply 230/115 V AC			1 Normally energized
		116 with relays, power supply 24 V DC			2 Normally de-energized
<input type="checkbox"/>	B	Measurement type, frequency range	<input type="checkbox"/>	H	Limit relay 2
		For vibration velocity sensors VS-068/069/0168/0169			1 Latching
		1 Vibration velocity, 10...1000 Hz			2 Non-latching
		2 Vibration velocity, 1...1000 Hz		<input type="checkbox"/>	I
		3 Vibration displacement, 10...1000 Hz			Relay time delay, Limit 1
		For vibration velocity sensors VS-077/078/079/177			1 1 sec
		4 Vibration velocity, 15...1000 Hz			2 3 sec
		5 Vibration velocity, 2...1000 Hz			3 10 sec
		6 Vibration displacement, 15...1000 Hz			4 30 msec
<input type="checkbox"/>	C	Measuring range	<input type="checkbox"/>	J	Relay time delay, Limit 2
		For vibration velocity, vibration displacement			1 1 sec
		1 0 ... 10 mm/s 0 ... 100 µm			2 3 sec
		2 0 ... 2 mm/s 0 ... 20 µm			3 10 sec
		3 0 ... 5 mm/s 0 ... 50 µm			4 30 msec
		4 0 ... 20 mm/s 0 ... 200 µm		<input type="checkbox"/>	K
		5 0 ... 50 mm/s 0 ... 500 µm			Limit setting acc. to customer data
		6 0 ... 100 mm/s 0 ... 1000 µm			1 No
<input type="checkbox"/>	D	Analogue outputs	<input type="checkbox"/>	L	Vibration velocity sensor
		1 0 ... 20 mA and 0 ... 10 V			1 Without Ex-protection
		2 4 ... 20 mA and 0 ... 10 V			2 With Ex-protection
<input type="checkbox"/>	E	Limit relay 1	<input type="checkbox"/>	M	Main power supply
		1 Normally energized			1 230 V AC 50/60 Hz
		2 Normally de-energized			2 115 V AC 50/60 Hz
<input type="checkbox"/>	F	Limit relay 1	<input type="checkbox"/>	N	Special requirements
		1 Latching			0 No
		2 Non-latching			1 Yes, following:

Works default settings

CV - A 110 / B 1 / C 1 / D 2 / E 2 / F 1 / G 2 / H 1 / I 1 / J 1 / K 1 / L 1 / M 1 / N 0 / Sum Code 125
 116 / 1 / 1 / 2 / 2 / 1 / 2 / 1 / 1 / 1 / 1 / 1 / 3 / 0 / 133

Customer-specific settings

CV - A / B / C / D / E / F / G / H / I / J / K / L / M / N / Sum Code